

CAPACITY:

13,000 BTUH (3.8kW)
80°F (27°C) – 140°F (60°C) ambient air temperature.

COMPRESSOR:

Open drive, reciprocating.

WELDED FRAME CONSTRUCTION:

16 gauge 0.06" (1.5mm)
Epoxy Painted.
Optional embossed 304 stainless steel frame.

CONDENSER COIL:

Aluminum fin, copper tube. 6 fins per inch (4.2mm).
Heavy gauge hardened fin stock 0.01" (0.254mm) thickness.
Epoxy coated.

MOTORS:

3.0 kW (4.0HP) Totally enclosed.
3.0HP for 250 VDC.
Suitable for high ambient applications.

VOLTAGES:

208-230/460/575/3/60 VAC
190,200/380,400,415/500/3/50 VAC
250 VDC

REFRIGERANT:

R-134a

CONTROLS:

High/Low Pressure Switch.
Crankcase Heater.
Receiver Tank for system pump down.
Pressure Relief Valve.

FANS:

Fiberglass reinforced nylon with
Aluminum hub.

WEIGHT:

300 lbs. (137 kg)



SEVERE DUTY AIR CONDITIONING

21334SC SELF-CONTAINED UNIT WHEN MOUNTED WITH EVAPORATOR

