

**CAPACITY:**

13,000 BTUH (3.8 kW)

Will operate up to 140°F (60°C) ambient air temperature.

**COMPRESSOR:**

Open Drive, Reciprocating.

**WELDED FRAME CONSTRUCTION:**

Welded tube frame epoxy painted.

Optional: Embossed 304 Stainless Steel.

**COILS:**

Aluminum fin, copper tube. **Epoxy coated.**

Heavy gauge .01" (0.254mm) hardened fin stock.

Condenser: 6 fins per inch (4.2mm fin spacing).

Evaporator: 8 fins per inch (3.2mm fin spacing).

**MOTORS:**

Condenser: 3 kW. (4 HP) totally enclosed. V.A.C.

3 HP. totally enclosed. V.D.C

Evaporator: Backward curved motorized impeller.

Optional high static blower for ducted applications.

**VOLTAGES:**

230/460/575/3/60 VAC

380-415/3/50 VAC

250 VDC

**REFRIGERANT:**

R-134a.

**HEAT:**

4KW Heat (13,660 BTUH)

**CONTROLS:**

Dual pressure switch.

Crankcase heater.

Optional Digital controls.

**WEIGHT:**

345 lbs. (156 kg)



**SEVERE DUTY AIR CONDITIONING**

