

CAPACITY:

11,500-29,000 BTUH (3,4kW-8,5kW) with
80°F (27°C) return air temperature.

MOUNTING CONFIGURATIONS:

Ceiling mounting, Roof mounting, Thru-wall mounting.

WELDED FRAME CONSTRUCTION:

14 gauge 0.075" (1.9mm) and 11 gauge 0.120" (3.04mm)
Embossed 304 stainless steel.

EVAPORATOR COIL:

Aluminum fin, copper tube. 8 fins per inch (3.2mm).
Heavy gauge hardened fin stock 0.0095" (0.241mm)
thickness. **Epoxy coated.**

BLOWER MOTOR:

1/4HP (0.19kW) or 1/2HP (0.37kW)
NEMA 56 frame TENV 960-1140/1450-1750 RPM.

VOLTAGES:

208-230/460/575/3/60 VAC
190,200/380,400,415/500/3/50 VAC
250 VDC

REFRIGERANT FLOW CONTROL:

Balance port thermostatic expansion valve.

HEATER:

4kW (13,660 BTUH.)

MECHANICAL AIR FILTER:

Polyester fiber throw-away filter.

REFRIGERANTS:

R-124 and R-134a.

WEIGHT:

140 LBS. (64kg.)

AIR FLOW:

1/4HP Motor: 430 CFM (60Hz), 345 CFM (50Hz)
1/2HP Motor: 630 CFM (60Hz), 550 CFM (50Hz)



