

**CAPACITY:**

20,000-65,000 BTUH (5.8kW – 19kW).  
50°F (10°C) – 135°F (57°C) Ambient air temperature.  
Variation in capacity dependent on compressor sizing,  
type of refrigerant, ambient operating temperature and  
return air temperature to evaporator.

**COMPRESSOR:**

“Copeland” hermetic Scroll.

**WELDED FRAME CONSTRUCTION:**

16 gauge 0.06” (1.5mm).  
304 Stainless Steel.

**COILS:**

Aluminum fin, copper tube. **Epoxy coated.**  
Heavy gauge .01” (0.254mm) hardened fin stock.  
Condenser: 8 fins per inch (3.2mm).  
Evaporator: 8 fins per inch (3.2mm).

**MOTORS:**

Condenser Fan: Axial fan.  
Evaporator: Backward curved motorized impeller.

**VOLTAGES:**

208-230/460/575/3/60 VAC  
380-415/3/50 VAC  
Single phase available on limited models.

**REFRIGERANT:**

R-134a

**HEAT:**

Optional 4KW, 6KW, 8KW or 10KW.

**FANS:**

Condenser: Axial Fan.  
Evaporator: Backward curved, motorized impeller.

**WEIGHT:**

520 lbs. (236 kg)



**HEAVY DUTY AIR CONDITIONING**

