

**CAPACITY:**

10,000 BTUH (2.9kW) Based on 95°F (35°C) evaporator return air temperature. For higher capacities we offer multiple evaporators for use with larger Lintern condenser sections.

**MOUNTING CONFIGURATIONS:**

Horizontally or vertically, front or back for mounting on an inside ceiling roof, inside wall of an office, or outside wall of a electrical enclosure.

**WELDED FRAME CONSTRUCTION:**

Heavy gauge embossed 304 stainless steel frame.

**EVAPORATOR COIL:**

Aluminum fin, copper tube. 8 fins per inch (3.2mm). Heavy gauge hardened fin stock 0.0095" (0.241mm) thickness. Epoxy coated.

**BLOWER WHEEL / MOTOR:**

Motorized impeller. Backward curved.

**VOLTAGES:**

380-460/3/50-60Hz, VAC  
208-230/1/50-60Hz, VAC

**REFRIGERANT FLOW CONTROL:**

Balance port thermostatic expansion valve.

**MECHANICAL AIR FILTER:**

Polyester fiber cleanable filter.

**REFRIGERANTS:**

R-124 and R-134a

**WEIGHT:**

50 LBS. (23kg.)

**Noise Level:**

60Hz 56dBA  
50Hz 52dBA



